



Double Submerged Spiral Arc Welded Pipes (DSSAW) ACC. To AWWA C200 & API 5L up to X70

Size (in)	Thickness (mm)																		
	5.60	6.40	7.10	7.90	8.70	9.50	10.30	11.10	11.90	12.70	14.30	15.90	17.50	19.10	20.60	22.20	23.80	25.40	
20	69.38						126.41					192.56							
22	76.42						139.37					212.95							
24		95.26						63.93					255.69						
26		103.15						177.62					277.27						
28		111.20							205.15						350.72				
30		119.25							220.12						376.63				
32		127.30							235.09							432.93			
34		135.35							250.05							460.85			
36					176.52				264.72							488.22			
38					186.46				279.69							516.14			
40					196.39				294.66							544.06			
42						227.05					371.22					571.98			
44						237.99					389.21					599.90			
46						248.72					406.84					627.27			
48						259.66					424.82					655.19			
52							307.25				460.79					711.03			
56							330.91				496.41					766.32			
60							354.80			473.31						822.16			
64							378.80			505.26						878.00			
68									503.30			670.91				933.30			
72										568.83			781.75					1059.49	
76										600.46			825.34					1118.76	
80											711.52			948.09					1256.86
84											747.35			995.94					1320.50
88											783.17			1043.80					1384.14
96												949.85			1228.23				1511.42
104												1029.52			1331.46				1638.69
112												1109.19			1434.68				1765.97
120												1188.87			1537.91				1893.25

