



High Frequency Induction Welded Pipe (HFI) ISO 3183 /API 5L Gr B,A,X42 - X65 PSL2

Size		Thickness mm	Weight kg/m
Nominal	in		
2 7/8	2.875	2.11	3.690
		2.77	4.791
		3.18	5.461
		3.58	6.131
		3.96	6.741
		4.37	7.395
		4.78	8.035
3 1/2	3.500	2.11	4.509
		2.77	5.878
		3.18	6.711
		3.58	7.529
		3.96	8.303
		4.37	9.107
		4.78	9.910
4	4.000	5.49	11.279
		2.11	5.178
		2.77	6.741
		3.18	7.708
		3.58	8.660
		3.96	9.538
		4.37	10.476
		4.78	11.398
4 1/2	4.500	5.74	13.571
		6.35	14.910
		2.11	5.833
		3.18	8.705
		3.58	9.776
		3.96	10.773
		4.37	11.844
		4.78	12.901
		5.16	13.868
		5.56	14.910
		6.02	16.070
6.35	16.904		
7.14	18.853		
7.92	20.787		
8.56	22.320		

Size		Thickness mm	Weight kg/m
Nominal	in		
5 9/16	5.563	2.11	7.232
		3.18	10.818
		3.96	13.422
		4.78	16.070
		5.56	18.615
		6.55	21.769
		7.14	23.615
		7.92	26.055
		8.74	28.555
		9.53	30.95
6 5/8	6.625	2.11	8.63
		2.77	11.294
		3.18	12.931
		3.58	14.538
		3.96	16.056
		4.37	17.663
		4.78	19.255
		5.16	20.743
		5.56	22.320
		6.35	25.356
8 5/8	8.625	7.11	28.257
		7.92	31.337
		8.74	34.373
		9.53	37.274
		3.18	16.904
		3.96	21.011
		4.78	25.236
		5.16	27.201
		5.56	29.284
		6.35	33.301
7.04	36.783		
7.92	41.262		
8.18	42.527		
8.74	45.310		
9.53	49.208		



High Frequency Induction Welded Pipe (HFI) ISO 3183 /API 5L Gr B,A,X42 - X80 PSL2

Size (in)	Thickness (mm)													
	4.00	4.80	5.60	6.40	7.10	7.80	8.70	9.50	11.10	11.90	12.70	15.90	17.50	20.60
8 5/8	21.22				36.61						64.64			
10 3/4		31.76				51.30						100.85		
12 3/4		37.77					67.62					120.76		
14		41.52						81.08				133.19		
16		47.54						92.98					167.83	350.72
18			62.34						122.05					221.69
20			69.38						136.01					246.60
22				87.21						160.55				273.51
24					105.56						264.72			299.10

